## State of Utah Technical Architecture Enterprise Intrusion Detection 2000.08.17

Title: Enterprise Intrusion Detection Standard

Introduction: Intrusion Detection services provide the ability to detect network attacks originating from the Internet. They also provide the ability to quickly shut off network attacks by making changes to the core network routers to deny access from the source device or network where the attack originates. The IDS scanner is a hardware platform that analysis every network packet against knows types of network attacks. Network attacks can be identified by key network characteristics, often called signatures. When a pattern is matched the scanner forwards the information to the IDS director, which provides alarm, notification, and the possibility of modifying router configurations to stop the attack. Common attack signatures are maintained in the scanner and periodically changed or updated. Attached is list of some of the more common signatures the sensor is configured to detect. Additional intrusion detection systems may be installed at State Agencies based upon the requirements identified in Agency Security Needs Analysis documents developed by ITS and related state agencies.

Rationale and Justification: Use of wide area networking (WAN) resources and the Internet has increased the opportunities for foreign access to the network, as well as the opportunity for hackers or unauthorized individuals to connect to State information systems. An enterprise intrusion detection system (IDS) is necessary to monitor, track, and possibly restrict access to the State WAN. Intrusion detection is an essential component of an overall integrated information security plan that also includes firewalls, VPNs, PKI, and Web specific security such as SSL, along with general computer security implementations to guard against unauthorized access and attacks. This standard will assist the State in integrating all these capabilities onto a consistent hardware / software platform to maximize business success and security.

**Application:** This standard is applicable to all executive government agencies in the State of Utah.

**Current Architecture:** A few agencies have investigated this technology for application at a Departmental level, however, there has been no enterprise implementations at present. At some locations individual computers have been protected with IDS software such as BlackICE by Network ICE.

**Future Architecture:** With the explosive growth of the Internet, the need for electronic communications, and the tremendous increase in hacker and security attacks, nearly every agency will recognize the critical need to protect their computing environments from attackers. This will be accomplished in two ways. 1) Implementation of an enterprise IDS system to look for a base level of attacks. 2) Securing individual servers and PCs to make them less prone to attacks. This can be accomplished by more tightly controlled local IDS configurations and/or software and configuration changes on individual computer systems.

## **Definitions:**

Signature: A pattern of network information that can be compared to a rule set indicating typical intrusion activity.

Authority: <u>Utah Code</u> Section 63D Information Technology Act.

National and International Standards References: none

**Technical Consideration(s):** With the installed base of Cisco routers and switches it is imperative that IDS solutions have tight integration with this environment. HP Openview is also

utilized extensively at the Enterprise level for network management. The Cisco IDS sensor and IDS Director tightly integrate with these environments allowing for the most flexibility to monitor, notify, and terminate network attacks. The IDS scanner operates on a hardened operating system focused on detecting network intrusion signatures and providing secure alarms to the IDS Director. Future blades for the Cisco Catalyst products will provide integrated IDS capabilities at the switch level. Management of the scanner, future switch blades, and the Director environment is supported at the centralized enterprise level.

**Exceptions:** Departments are authorized to implement their own network and computer based detection systems to meet the needs of their specific security policies.

**Gap Analysis:** Specific agency security requirements may identify a need for Departmental IDS capabilities. These requirements can be handled by separate projects and budgeting at the Department level. This does not represent a major impact to the WAN.

**Approved Configurations:** For the Enterprise installation the Cisco IDS Scanner and IDS Director are deemed necessary. Individual Departmental configurations may utilize this, or other vendor's solutions to meet the specific agency security requirements.

**Migration and Implementation Plan:** All new purchases of IDS products will be expected to be in full compliance with this standard.

**Review Cycle:** This standard will be reviewed and updated on an annual basis, based upon the CIO approval date.

State Purchasing Contracts: Cisco IDS products are available under the following contracts:

Contract Number	Description	Vendor
AR-637	LAN/WAN (US West Router Contract)	Qwest
AR-794	LAN/WAN (US West Switch Contract)	Qwest
AR-877	LAN/WAN Switch Contract	Mountain States Networking

## References:

Interim Date: August 17, 2000

Organization Sponsoring the Standard: State Information Security Committee (SISC)

State Technical Architect Approval Date: Pending

CIO Approval Date: Pending

ITPSC Presentation Date: October 19, 2000

**Author(s):** Joe Leary (ITS)

**Addendum:** The following is a list of basic attack signatures the IDS Scanner is programmed to detect.

1000 - IP options-Bad Option List

1001 - IP options-Record Packet Route

1002 - IP options-Timestamp

1003 - IP options-Provide s,c,h,tcc

1004 - IP options-Loose Source Route

1005 - IP options-SATNET ID

1006 - IP options-Strict Source Route

1100 - IP Fragment Attack

1101 - Unknown IP Protocol

1102 - Impossible IP Packet

1103 - IP Fragments Overlap

2000 - ICMP Echo Reply

2001 - ICMP Host Unreachable

- 2002 ICMP Source Quench
- 2003 ICMP Redirect
- 2004 ICMP Echo Request
- 2005 ICMP Time Exceeded for a Datagram
- 2006 ICMP Parameter Problem on Datagram
- 2007 ICMP Timestamp Request
- 2008 ICMP Timestamp Reply
- 2009 ICMP Information Request
- 2010 ICMP Information Reply
- 2011 ICMP Address Mask Request
- 2012 ICMP Address Mask Reply
- 2100 ICMP Network Sweep w/Echo
- 2101 ICMP Network Sweep w/Timestamp
- 2102 ICMP Network Sweep w/Address Mask
- 2150 Fragmented ICMP Traffic
- 2151 Large ICMP Traffic
- 2152 ICMP Flood
- 2153 Smurf
- 2154 Ping of Death Attack
- 3000 TCP Ports
- 3001 TCP Port Sweep
- 3002 TCP SYN Port Sweep
- 3003 TCP Frag SYN Port Sweep
- 3005 TCP FIN Port Sweep
- 3006 TCP Frag FIN Port Sweep
- 3010 TCP High Port Sweep
- 3011 TCP FIN High Port Sweep
- 3012 TCP Frag FIN High Port Sweep
- 3015 TCP Null Port Sweep
- 3016 TCP Frag Null Port Sweep
- 3020 TCP SYN FIN Port Sweep
- 3021 TCP Frag SYN FIN Port Sweep
- 3030 TCP SYN Host Sweep
- 3031 TCP FRAG SYN Host Sweep
- 3032 TCP FIN Host Sweep
- 3033 TCP FRAG FIN Host Sweep
- 3034 TCP NULL Host Sweep
- 3035 TCP FRAG NULL Host Sweep
- 3036 TCP SYN FIN Host Sweep
- 3037 TCP FRAG SYN FIN Host Sweep
- 3038 Orphaned Fin Packet
- 3039 Fragmented Orphaned FIN packet
- 3040 NULL TCP Packet
- 3041 Fragmented NULL TCP Packet
- 3042 SYN/FIN Packet
- 3043 Fragmented SYN/FIN Packet
- 3045 Queso Sweep
- 3050 Half-open SYN Attack
- 3100 Smail Attack
- 3101 Sendmail Invalid Recipient
- 3102 Sendmail Invalid Sender
- 3103 Sendmail Reconnaissance
- 3104 Archaic Sendmail Attacks
- 3105 Sendmail Decode Alias
- 3106 Mail Spam
- 3107 Majordomo Execute Attack

- 3108 MIME Overflow Bug
- 3109 Q-Mail Length Crash
- 3150 FTP Remote Command Execution
- 3151 FTP SYST Command Attempt
- 3152 FTP CWD ~root
- 3153 FTP Improper Address Specified
- 3154 FTP Improper Port Specified
- 3200 WWW Phf Attack
- 3201 WWW General cgi-bin Attack
- 3202 WWW .url File Requested
- 3203 WWW .Ink File Requested
- 3204 WWW .bat File Requested
- 3205 HTML File Has .url Link
- 3206 HTML File Has .lnk Link
- 3207 HTML File Has .bat Link
- 3208 WWW campas Attack
- 3209 WWW Glimpse Server Attack
- 3210 WWW IIS View Source Attack
- 3211 WWW IIS Hex View Source Attack
- 3212 WWW NPH-TEST-CGI Attack
- 3213 WWW TEST-CGI Attack
- 3214 IIS DOT DOT VIEW Attack
- 3215 IIS DOT DOT EXECUTE Attack
- 3216 IIS Dot Dot Crash Attack
- 3217 WWW php View File Attack
- 3218 WWW SGI Wrap Attack
- 3219 WWW PHP Buffer Overflow
- 3220 IIS Long URL Crash Bug
- 3221 WWW cgi-viewsource Attack
- 3222 WWW PHP Log Scripts Read Attack
- 3223 WWW IRIX cgi-handler Attack
- 3224 HTTP WebGais
- 3225 HTTP Gais Websendmail
- 3226 WWW Webdist Bug
- 3227 WWW Htmlscript Bug
- 3228 WWW Performer Bug
- 3229 Website Win-C-Sample Buffer Overflow
- 3230 Website Uploader
- 3231 Novell convert
- 3232 WWW finger attempt
- 3233 WWW count-cgi Overflow
- 3250 TCP Hijack
- 3251 TCP Hijacking Simplex Mode
- 3300 NetBIOS OOB Data
- 3301 NETBIOS Stat
- 3302 NETBIOS Session Setup Failure
- 3303 Windows Guest Login
- 3304 Windows Null Account Name
- 3305 Windows Password File Access
- 3306 Windows Registry Access
- 3307 Windows Redbutton Attack

- 3400 Sunkill
- 3450 Finger Bomb
- 3450 Finger Bomb
- 3500 Rlogin -froot Attack
- 3525 IMAP Authenticate Buffer Overflow
- 3526 Imap Login Buffer Overflow
- 3550 POP Buffer Overflow
- 3575 INN Buffer Overflow
- 3576 INN Control Message Exploit
- 3600 IOS Telnet Buffer Overflow
- 3601 IOS Command History Exploit
- 3602 Cisco IOS Identity
- 3602 Cisco IOS Identity
- 4000 UDP Packet
- 4001 UDP Port Sweep
- 4002 UDP Flood
- 4050 UDP Bomb
- 4051 Snork
- 4052 Chargen DoS
- 4053 Back Orifice
- 4054 RIP Trace
- 4100 Tftp Passwd File
- 4150 Ascend Denial of Service
- 4600 IOS UDP Bomb
- 5034 WWW IIS newdsn attack
- 5035 HTTP cgi HylaFAX Faxsurvey
- 5036 WWW Windows Backup Password File Access Attempt
- 5036 WWW Windows Password File Access Attempt
- 5037 WWW SGI MachineInfo Attack
- 5038 WWW wwwsgl file read Bug
- 5039 WWW finger attempt
- 5040 WWW perl interpreter attack
- 5040 WWW perl interpreter attack
- 5040 WWW perl interpreter attack
- 5041 WWW anyform attack
- 5042 WWW CGI Valid Shell Access
- 5042 WWW CGI Valid Shell Access
- 5042 WWW CGI Valid Shell Access
- 5042 WWW CGI Valid Bourne Shell Attack
- 5042 WWW CGI Valid Java Shell Attack
- 5042 WWW CGI Valid Python Shell Attack
- 5043 WWW Cold Fusion Attack
- 5043 WWW Cold Fusion Attack
- 5043 WWW Cold Fusion Attack
- 5044 WWW Webcom.se Guestbook attack
- 5045 WWW xterm display attack
- 5046 WWW dumpenv.pl recon
- 5047 WWW Server Side Include POST attack
- 5048 WWW IIS BAT EXE attack
- 5048 WWW IIS BAT EXE attack
- 5049 WWW IIS showcode.asp access
- 5050 WWW IIS .htr Overflow Attack
- 6001 Normal SATAN Probe
- 6002 Heavy SATAN Probe
- 6050 DNS HINFO Request
- 6051 DNS Zone Transfer

- 6052 DNS Zone Transfer from High Port
- 6053 DNS Request for All Records
- 6055 DNS Inverse Query Buffer Overflow
- 6100 RPC Port Registration
- 6101 RPC Port Unregistration
- 6102 RPC Dump
- 6103 Proxied RPC Request
- 6104 RPC Set Spoof
- 6110 RPC RSTATD Sweep
- 6111 RPC RUSERSD Sweep
- 6112 RPC NFS Sweep
- 6113 RPC MOUNTD Sweep
- 6114 RPC YPPASSWDD Sweep
- 6115 RPC SELECTION\_SVC Sweep
- 6116 RPC REXD Sweep
- 6117 RPC STATUS Sweep
- 6118 RPC ttdb Sweep
- 6150 ypserv Portmap Request
- 6151 ypbind Portmap Request
- 6152 yppasswdd Portmap Request
- 6153 ypupdated Portmap Request
- 6154 ypxfrd Portmap Request
- 6155 mountd Portmap Request
- 6175 rexd Portmap Request
- 6180 rexd Attempt
- 6190 statd Buffer Overflow
- 6191 RPC.tooltalk buffer overflow
- 6192 RPC mountd Buffer Overflow
- 6200 Ident Buffer Overflow
- 6201 Ident Newline
- 6202 Ident Improper Request
- 6250 FTP Authorization Failure
- 6251 Telnet Authorization Failure
- 6252 Rlogin Authorization Failure
- 6253 POP3 Authorization Failure
- 6255 SMB Authorization Failure
- 6300 Loki ICMP Tunnelling
- 6302 General Loki ICMP Tunneling
- 8000 FTP Retrieve Password File
- 8000 Telnet-IFS Match
- 8000 Telnet-/etc/shadow Match
- 8000 Telnet-+ +
- 8000 Rlogin-IFS Match
- 8000 Rlogin-/etc/shadow Match
- 8000 Rlogin-+ +
- 10000 IP-Spoof Interface 1
- 10000 IP-Spoof Interface 2